



## Xtech 5W-30

### Fully Synthetic

**Recommended by Comma for applications requiring:**

FORD WSS-M2C913-D, WSS-M2C913-C, WSS-M2C913-B, WSS-M2C913-A  
ACEA A5/B5; API SL CF

**Product Features:**

- Fully synthetic, high performance 5W-30 oil, for Ford DuraTec, DuraTorq and Zetec Vehicles, offering the fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Typical Inspection Data:

Density @ 20°C	0.848
Viscosity @ 100°C	9.9 cSt
Viscosity @ 40°C	55 cSt
Viscosity Index	166
Viscosity CCS @ -30°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

29-04-2015