

**SCREW COMPRESSORS EVERT PLUS 5,5 – 15kw****Powered by Airpress**

Compressed air drives most of the businesses, consequently choosing the right compressor is one of the most important decisions your company can make. Our Evert 5,5-15kw range is a robust and reliable belt driven oil-injected screw compressor – a first class product that can be easily equipped with an air receiver, a refrigerant dryer, pre and post filters, offering you a compact and complete solution for your business.



Complete Solution

Very compact all in one design:

- base mounted unit requires less than a square meter,
- available on air receiver,
- also with dryer and filters if needed.

Full protected for transport:

No special foundation required,

Very low vibration and noise level (65 – 71 dB(A),

Easily installed inside the workshop, very close to the air usage point.

Legendary reliability

Robust and reliable design

Built with first-class components (atlas copco, weg, nema, Siemens)

New generation of rotary screw element allows you to work on 100% continuous duty cycles and very hard working conditions,

An oversized ventilation ensures low internal temperatures, making your compressor live better and longer,

The complete unit is designed to operate at ambient temperatures up to 46°C / 115° F

Easy maintenance and accessibility

All service components located at the front of the machine for excellent accessibility,

All service components strategically located for excellent accessibility,

Oil-level sight glass at the front, visible without removing any panel,

Service and cleaning is a one person job.

Cost Efficiency

Reliable design

Low maintenance costs

Long service intervals

Low Energy consumption, thanks to reputed IE3 Motors and advanced screw compressor element,

High performing lubrication and cooling systems.

Intelligent monitoring control and protection - Infologic2



The Infologic 2 controller offers advanced monitoring and simple day-today configuration and control for your operation.

- Icon-based display with pressure and temperature reading,
- Running hours, load hours,
- Maintenance warnings,
- Failure alarms,
- Fast pressure setting directly on the controller,
- Remote start-stop
- Automatic restart after power failure,

TECHNICAL DATA: EVERT PLUS 5,5-15kw

model	ciś. Maks.	wydajność efektywna		zasilanie	moc silnika		głośność
	max pressure	Free air delivery		Voltage	motor power		noise level
	bar	m3/h	l/min	V/Hz/Ph	kw	HP	dB(A)
EVERT5,5	8	50,8	847	400/50/3	5,5	7,5	64
	10	41,8	680				
EVERT7,5	8	68,4	1140	400/50/3	7,5	10	65
	10	59,8	997				
	13	46,8	780				
EVERT11	8	97,2	1620	400/50/3	11	15	69
	10	85	1417				
	13	69,1	1152				
EVERT15	8	111,6	1860	400/50/3	15	20	71
	10	100,8	1680				
	13	79,9	1332				

**DIMENTIONS**

model	INDEKS CODE	waga weight kg	zbiornik tank L	osuszacz dryer	długość length mm	szerokość width mm	wysokość Height mm
EVERT5,5+		160	-	-	850	720	980
EVERT5,5/500+		257	500	-	1945	720	1468
EVERT5,5/500/D+		292	500	v	1945	720	1468
EVERT7,5	IC-C58CF4	170	-	-	850	720	980
EVERT7,5/500	IC-C013D0	267	500	-	1945	720	1468
EVERT7,5/500/D	IC-C39948	300	500	v	1945	720	1468
EVERT11	IC-C58CE7	185	-	-	850	720	980
EVERT11/500	IC-C013CE	282	500	-	1945	720	1468
EVERT11/500/D	IC-C3994B	315	500	v	1945	720	1468
EVERT15	IC-D48B09	200	-	-	850	720	980
EVERT15/500	IC-D48B0B	297	500	-	1945	720	1468
EVERT15/500/D	IC-D48B0C	330	500	v	1945	720	1468