

Automatic Transmission Flush

Product properties

Reliably dissolves and removes contamination, oxidised oil residues and other deposits from the entire gear oil system. The whole system is thoroughly cleaned.

- Complete removal of contaminants
- Reduces unpleasant noises and ensures a safe and smooth operation of the transmission
- Optimizes the switching behavior
- Avoid costly repairs

WHY USE?

Today's gear oils are usually of good quality but they can not prevent, that operationally caused contaminations and oxidized oil residues deposited with time on the transmission parts. Result: performance degradation and switching problems. The system runs rough and dirty parts are loaded higher. Our Automatic Transmission Flush will help. The product is suitable for all automatic transmission oils.

Area of application

In all kinds of automatic transmissions

Application

Add the product to the oil system before exchanging the gear oil. Run the system for approx. 10-15 minutes under frequent load alteration. Afterwards carry out the exchange of the gear oil in accordance to the manufacturer's instructions.

Consumption

375 ml for cars / approx. 5% of the transmission oil volume for trucks

Reaction time

approx. 15 minutes

Technical data

Physical state: liquid

Colour: yellow

Odour: aromatic

Initial boiling point and boiling range: 180 - 220 °C

Flashpoint: 63 °C

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.82 - 0.90 g/cm³

Available sizes	Item no.	PU
375ml	33179	28



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advice. No liability for any printing errors. Technical modifications and errors are exempted.