

ANTICORIT DFG

Corrosion Preventive – Spraying Oil with anti wear additives

Description

ANTICORIT DFG is a multipurpose oil with excellent corrosion protection and penetrating properties. After the solvent has evaporated, ANTICORIT DFG forms a highly-viscous, non-dripping and non-resinating film.

ANTICORIT DFG has dewatering properties and contains molybdenum disulphide and graphite to reduce wear.

ANTICORIT DFG is perfect for difficult-to-reach lubrication spots. It has very good penetrating properties and loosens tight threads, hinges and joints. ANTICORIT DFG lubricates and protects reliably against corrosion.

Application

ANTICORIT DFG may be applied by brushing, spraying or dipping. The valid safety regulations have to be taken into account. Anti wear agents may settle down during long storage periods. Original quality can be restored by stirring.

ANTICORIT DFG is also available in spray cans.

Benefits

- Protects against corrosion
- Contains molybdenum disulphide and graphite
- Penetrating properties
- Excellent properties

Storage conditions

If sealed in the original container ANTICORIT DFG can be stored up to 12 months at temperatures between - 20 °C to + 40 °C.

The indication of a minimum period of storage does not include any guarantee of durability.

ANTICORIT DFG

Corrosion Preventive – Spraying Oil with anti wear additives

Typical chemical and physical properties:

Property	Unit	Data	Test method
Density at 15 °C	kg/m ³	851	DIN 51 757
Flashpoint	°C	94	DIN EN ISO 2719
Film weight	g/m ²	4.0	FLV-F-03 *)

The above data is typical of normal production and should not be taken as a specification.

*) FLV = Test procedure of FUCHS SCHMIERSTOFFE GMBH