

Product Information

MOVING YOUR WORLD



FUCHS MAINTENANCE SPRAY

(Formerly known as ANTICORIT 988 AEROSOL)

A Multi-Purpose Rust Preventive, Lubricant and Dewatering Aerosol

Description

FUCHS MAINTENANCE SPRAY is a product from the FUCHS Lubricants (UK) range of industrial aerosol packaged products. It is used for dewatering and protection of metallic components after water treatment, as well as for light lubricating applications.

Application

FUCHS MAINTENANCE SPRAY is useful for cleaning and protecting most electrical equipment. Other typical applications include lubrication of small or inaccessible components, such as locks and hinges and loosening of rust scale before wire-brushing.

After drying, the product, which contains corrosion inhibitors, leaves an almost dry, slightly oily film. It is also highly penetrative which aids its usefulness as a water displacing agent and light lubricant. The product conforms to the requirements of British Standard Specification BS1133 TP 2b. It has a variety of uses industrially, as a rust inhibitor FUCHS MAINTENANCE SPRAY is superb and, after one application, rusting and scaling can be removed with a wire brush. Where there is particularly heavy or stubborn rusting, a second application may be necessary to help remove the corrosion and leave the metal surface fully protected with a micro-thin only film.

Advantages/Benefits

- Large 500ml aerosol can
- Provides an ultra-thin anti-corrosion protective film
- Medium drying properties
- Lubricates and penetrates
- Excellent dewatering fluid
- After drying, treated items are not slippery or difficult to handle
- Contains no CFC propellants - ozone friendly

Specifications

- BS1133 Classification TP 2b

Cleaning

Fuchs recommends the use of our fully compatible RENOCLEAN cleaners to clean your components. Please refer to data sheets or contact your local Fuchs Area Manager to discuss your requirements.

Product Information

MOVING YOUR WORLD



Directions for Use

Shake the can thoroughly before use

Hold in an upright position, spraying directly onto the component surface from a distance of 8-12 inches

The highly directional button ensures accurate positioning of the lubricant

Always ensure any guarding is in place when treating moving equipment

Re-apply as required

Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.

Caution

- Pressurised container
- Protect from sunlight and do not expose to temperatures exceeding 50°C
- Do not pierce or burn, even after use
- Do not spray on a naked flame, or any incandescent material

NOTE

Follow the safety information printed on the cans to ensure safe application.