

Diesel Conditioner & Anti-Gel 1:1000

Product properties

High performance diesel system protection for improving the flow of diesel fuels suitable for all engine systems such as common rail or direct injection. Winter-proof up to -27.4 °F (depending on the quality of the fuel). The thickening of the diesel fuel in extreme cold conditions is prevented and thus the operational reliability is increased especially in the winter. Fuel filters and pipes are provided from clogging and this improves cold-start performance and warm-up phase. Optimal lubrication of all moving parts of the Diesel Systems.

Area of application

For use in diesel powered engines. Recommended for engines with particle filter, turbo and catalytic converter.

Application

Fill directly into the diesel tank. Observe mixing ratio. Apply as possible at temperatures above 32 °F and before the diesel is gelling. At temperatures below -4 °F can no longer be ensured mixing with the diesel fuel. Store frostproof!

Consumption

1 liter sufficient for 1000 liters diesel. Mixing ratio 1:1000

Reaction time

while engine is running

Technical data

Physical state: liquid

Colour: clear/colourless

Odour: characteristic

Pourpoint: -9 °C

Flashpoint: 62 °C

not Explosive

Density at 68 °F: 0,84 - 0,86 g/cm³

Viscosity / kinematic (at 104 °F): 12,7 mm²/s

Available sizes	Item no.	PU
300ml	51098	24
1L	51101	12
5L	51090	4
10L	51094	1
20L	51096	1
200L	51099	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.